

TIPO S





TABLA DIMENSIONAL
Medidas en mm

Eje mm	d ₃	l ₁
12.0	21.0	7.5
12.7	21.0	7.5
14.0	23.0	7.5
15.0	24.0	7.5
15.8	25.0	7.5
16.0	25.0	7.5
18.0	31.0	7.5
19.1	31.0	7.5
20.0	33.0	7.5
22.0	35.0	7.5
22.2	35.0	7.5
24.0	37.0	7.5
25.0	38.0	7.5
25.4	38.0	7.5
28.0	41.0	7.5
28.6	41.0	7.5
30.0	43.0	7.5
31.7	45.0	7.5
32.0	45.0	10.0
33.0	46.0	10.0
35.0	48.0	10.0
38.0	53.0	10.0
40.0	55.0	10.0

SECTORES:



CARACTERÍSTICAS:

- Anillo con dos tornillos allen de fijación al eje.

DESCRIPCIÓN:

Este elemento se fija al eje para asegurar permanentemente la compresión de la parte rotante del sello mecánico.

Puede utilizarse con cierres mecánicos de fuelle de goma o muelle simple.

Eje mm	d ₃	l ₁
41.2	55.0	10.0
43.0	58.0	10.0
44.4	60.0	10.0
45.0	60.0	10.0
47.6	63.0	10.0
48.0	63.0	10.0
50.0	65.0	10.0
50.8	65.0	10.0
53.0	68.0	10.0
53.9	68.0	10.0
55.0	70.0	10.0
57.1	70.0	10.0
60.0	79.0	10.0
60.3	79.0	10.0
63.5	82.0	10.0
65.0	84.0	12.0
66.6	84.0	12.0
69.8	89.0	12.0
70.0	89.0	12.0
73.0	95.0	12.0
75.0	98.0	12.0
76.2	98.0	12.0

Medidas sujetas a variaciones o modificaciones.